

# VULCAN AGRI



Rubber Track for

## CASE QUADTRAC

30"6"42    36"6"42

Reference	Width	Lenght	Tread	Pitch	Tread height	Tread width	Guide lugs	Ply	Thickness
30"6"42	30"	252"	84	6"	2.6"	2"	42	4	1.5"
	762mm	640cm	84	152mm	65mm	50mm	42	4	38mm
36"6"42	36"	252"	84	6"	2.6"	2"	42	4	1.5"
	914mm	640cm	84	152mm	65mm	50mm	42	4	38mm



### ONE STEP VULCAN

**Vulcanisation in one step** of track core, guide lugs and tread patterns reinforce solidity and **prevent tread pull off**. All track parts are strongly vulcanised and bonded together. **Low wearability rubber compound** offers extended lifetime.



### STRONG CABLES

The track tensile strength is ensured by a full **layer of 5.4mm, seamless tension cables**. In addition, the track's core is reinforced with as much as **four steel cable layers** placed at special angles to maximise the core stiffness, making our tracks the **best choice for durability and flexibility**.



### ENGINEERED QUALITY

New **self-cleaning tread bars** improve traction whilst offering no vibrations. The tracks are designed to last and come with up to **2 years warranty** on Friction and Positive Drive Machines.

LEACH LEWIS RUBBER TRACKS LTD

UK: Units 4-5 Hikers Way, [Crendon Industrial Park](#), Long [Crendon](#) HP18 9RW

FRANCE: 58 Avenue De Wagram | 75017 PARIS

Commercial contact : Tel : +33 4 92 34 49 76 Email : [rb@llrt.co.uk](mailto:rb@llrt.co.uk)

[www.llrt.co.uk](http://www.llrt.co.uk)

